

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 350 567 A1

(12)

EUROPEAN PATENT APPLICATION
published in accordance with Art. 158(3) EPC

(43) Date of publication:
08.10.2003 Bulletin 2003/41

(51) Int Cl.⁷: **B01J 37/00, B21D 47/00,
F01N 3/28**

(21) Application number: **01982798.9**

(86) International application number:
PCT/JP01/09999

(22) Date of filing: **16.11.2001**

(87) International publication number:
WO 02/040157 (23.05.2002 Gazette 2002/21)

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **ICHIKAWA, Yukihiro,**
c/o NGK INSULATORS, LTD.
Nagoya-shi, Aichi 467-8530 (JP)
• **ITO, Eiji, c/o NGK INSULATORS, LTD.**
Nagoya-shi, Aichi 467-8530 (JP)

(30) Priority: **17.11.2000 JP 2000351679**

(71) Applicant: **NGK INSULATORS, LTD.**
Nagoya-shi Aichi 467-8530 (JP)

(74) Representative: **Page, Hugh Charles Edward**
MEWBURN ELLIS
York House
23 Kingsway
London WC2B 6HP (GB)

(54) **PROCESSING METHOD UTILIZING DISPLAY INFORMATION AND CELL STRUCTURE
PROCESSED BY THE PROCESSING METHOD**

(57) This is directed to a processing method for carrying a cell structure (1) with a catalytic component. Information about a mass of the cell structure (1) is displayed on the surface thereof prior to the initiation of a carrying process, and in the carrying process, the information is read and the cell structure (1) is carried with an appropriate amount of the catalytic component on the basis of the information. When cell structures are processed for carrying thereon a catalytic component, each cell structure can carry an appropriate amount of the catalytic component in accordance with the mass of the cell structure, even if there is a variation in the masses of the cell structures.

FIG. 1(a)





FIG. 1(b)



EP 1 350 567 A1

Description

Technical Field

[0001] The present invention relates to a processing method for carrying an appropriate amount of a catalytic component on a cell structure. The present invention can be applied to a catalyst carrier or a filter for use in purifying or deodorizing an exhaust gas of an internal combustion engine, or to a catalyst carrier or a filter for use in a chemical reaction instrument taking advantage of catalytic action such as a reformer of a fuel cell or the like.

Background Art

[0002] As an assembly employed for use in a catalytic converter, a filter, a heat exchanger or the like used for purifying the exhaust gas from an internal combustion engine or used for a chemical reaction instrument taking advantage of catalytic action, there have been known articles in which cell structures are held by and housed in metallic containers (canning) by interposing a compressive material having a cushioning property between the cell structure and the metallic container (a can body) and thereby giving a prescribed compressive contact stress to the cell structure through the compressive material.

[0003] For example, in the case where such an assembly is used as a catalytic converter for use in purifying automobile exhaust gas, a ceramic honeycomb structure, a type of cell structure, in which noble metals such as platinum, palladium, rhodium, or the like are dispersed and carried as catalytic components, is held by and housed in a metallic container (a can body) through the intermediary of a ceramic mat or the like, and is mounted in an exhaust system.

[0004] As in the above-described catalytic converter, in the case where a catalytic component is carried in the cell structure, an appropriate amount to be carried varies, depending on the masses of the cell structures. Conventionally, the masses of the cell structures are measured beforehand and the cell structures are sorted into several classes based on mass, and the amount of the carried catalytic component (the mass of the catalytic component) is adjusted so as to become the fixed value by controlling the masses after the catalytic component has been carried based on each class of the mass. However, since the masses of the cell structures have a certain variation even within the same class of the mass range, actually some variance exists in the carried amount of the catalytic component if it is examined at the individual cell structures.

[0005] The present invention has been completed, in view of the above described problems in the prior art, and the object thereof is to provide a processing method for carrying a catalytic component on each cell with an appropriate amount thereof in accordance with the

mass of the cell structure, at the time when the processing for carrying a catalyst component on the cell structure is done, even if there is a variation in the mass of the cell structure.

Disclosure of the Invention

[0006] According to the present invention, there is provided a processing method (a first invention) for carrying a catalytic component on a cell structure, characterized by displaying information about a mass of a cell structure on the surface thereof prior to the initiation of carrying process, reading the information and carrying the cell structure with an appropriate amount of a catalytic component on the basis of the information in the carrying process.

[0007] Additionally, according to the present invention, there is provided a processing method (a second invention) for carrying a cell structure having been housed in and held by a metallic container via a compressive material having a cushioning property with a catalytic component,

characterized by displaying information about a mass of a cell structure on the surface thereof prior to the initiation of carrying process, reading the information and carrying the cell structure with an appropriate amount of a catalytic component on the basis of the information in the carrying process.

[0008] Furthermore, according to the present invention, there is provided a cell structure (a third invention) processed according to any of the above described processing methods.

[0009] Yet furthermore, according to the present invention, there is provided a cell structure (a fourth invention), having the above described information displayed thereon, which is processed according to any of the above described processing methods.

Brief Description of the Drawings

[0010]

Figures 1(a) and (b) are illustrative views of a honeycomb structure used as a cell structure in an embodiment, Figure 1(a) being a plane view and Figure 1(b) an oblique perspective view.

Figure 2 is a diagram illustrating a method of marking barcodes by means of a laser marker device.

Best Mode for Carrying Out the Invention

[0011] As described above, a first invention as a processing method for carrying a catalytic component on a cell structure is characterized by displaying information about mass of a cell structure on the surface thereof prior to the initiation of the carrying process, reading the information, and carrying the cell structure with an appropriate amount of the catalytic component

on the basis of the information, in the carrying process.

[0012] By controlling the carried amount of the catalytic component on the basis of the information about the mass of the cell structure displayed on the surface of the cell structure, an appropriate amount of the catalytic component may be carried in accordance with the actual mass of the cell structure, and consequently carrying an excess amount of catalytic component can be avoided and the catalytic component amount can be saved.

[0013] In the first invention, characters and barcodes may be used for in the manner for displaying the information. Additionally, the information may be displayed by ink coating, a laser, sand blast, chemical corrosion, or the like. When the information is displayed by ink, it is preferable to use an ink jet method or a thermal transcription method.

[0014] As a cell structure, there is preferably used a honeycomb structure having a plurality of cell passages defined by a plurality of partition walls, the thickness of cell partition wall of 0.11 mm or less and the opening ratio of 85% or more. Furthermore, as the honeycomb structure, it is preferable that the structure has an outer wall forming an outer diameter contour around the structure, with the thickness of the outer wall being at least 0.05 mm. Incidentally, the cell structures used in the present invention may include a foamed structure, in addition to the honeycomb structures as described above.

[0015] It is preferable that the cell structure is made of a ceramic material or a compound comprising two or more ceramic materials selected from the group consisting of cordierite, alumina, mullite, lithium aluminum silicate, aluminum titanate, titania, zirconia, silicon nitride, aluminum nitride, and silicon carbide. Additionally, there can be suitably used a cell structure which is made of one adsorptive material selected from the group consisting of activated charcoal, silica gel, and zeolite.

[0016] Incidentally, the cell shape of a honeycomb structure produced by extrusion includes a trigon, a tetragon, a hexagon, a circle, or the like; in general, there are frequently used honeycomb structures having cells each shaped in a square, namely in a tetragon, but recently there have been increasingly used the honeycomb structures having hexagonal cells.

[0017] In the case where a cell structure is used as a catalytic converter, it is necessary to carry the cell structure with a catalytic component, and the cell structure is housed in and held by a metallic container usually after the cell structure has been carried with the catalytic component; however, as in the following second invention, the cell structure may be made to carry thereon the catalytic component after the cell structure has been housed in and held by the metallic container.

[0018] The second invention is characterized by carrying a cell structure having been held by and housed in a metallic container through a compressive material having a cushioning property with a catalytic component, in the processing method for carrying the cell

structure with the catalytic component, displaying information about the mass of the cell structure on the surface of the metallic container prior to the initiation of the carrying process, reading the information and carrying the cell structure with an appropriate amount of the catalytic component on the basis of the information, in the carrying process.

[0019] In the other words, the second invention controls the carried amount of the catalytic component based on the information about the mass of the cell structure, similarly to the first invention; however, the catalytic component is carried after the cell structure has been housed in and held by the metallic container, and accordingly the information display position is located on the metallic container surface but not on the cell structure surface which is made hidden in the metallic container. The action effect attained in the second invention is similar to the effect attained in the above described first invention.

[0020] Incidentally, in the first and second inventions, there can be used the display manners and display measures similar to those in the above described first invention.

[0021] A third invention is the cell structure processed according to the method related to the above described first or second invention, which is made to carry an appropriate amount of a catalytic component as described above, and accordingly can be suitably employed for use in the catalytic converter for purifying the automobile exhaust gas or the like. Additionally, a fourth invention is the cell structure before processing which is to be processed according to the method related to the above described first invention and has the information displayed thereon; the information is displayed thereon beforehand through the above described various manners and measures, and the processing method of the first invention is realized on the basis of the information. The suitable structures, materials or the like for the cell structure are as described above.

(Examples)

[0022] Further detailed description will be made below on the present invention, with reference to an example of the case in which a catalytic converter is produced by use of a honeycomb structure 1 as shown in Figure 1(a) and (b) as the cell structure; however, the present invention is not limited to these examples.

[0023] As for the methods of making the information such as characters and barcodes be displayed on a honeycomb structure, the method based on an ink jet printing device and the method based on a laser device are preferable for the purpose of processing a large number of members, because these methods are fast and of the non-contact type printing. Particularly, a laser based method is more preferable than the ink jet method from the viewpoint of maintenance because it does not need any ink and does not require any pre-processing to be

made beforehand.

[0024] The examination of the mass of a honeycomb structure is performed at the end of the production process of the honeycomb structure, and the information about the mass thereof examined and measured is made to be directly transmitted from the measurement instrument to a laser marker device. As shown in Figure 2, a honeycomb structure 1 having left the measurement instrument is then delivered to the laser marker device 3 where marking of the barcodes is made on the outer surface of the honeycomb structure 1 on the basis of the information about the mass simultaneously transmitted. A QR code is more preferable because it is small in marking area and accordingly requires a short marking time, and is hardly affected by the outer surface curvature of the honeycomb structure.

[0025] An example of the laser marking conditions will be described below. Incidentally, a YAG pulsed laser device or a CO₂(carbon dioxide) gas laser device is suitable as a laser marker device.

- Laser marker device:

A YAG laser marker device (manufactured by Miyachi Technos Corp., lamp excitation type, ML-4141B)

- Honeycomb structure:

A cordierite based honeycomb structure (partition wall: 2 mil; cell density: 900 cps; nominal outer diameter ϕ : 106 mm; length: 114 mm)

- Marking conditions:

Current value: 17A; Q. SW frequency: 8kHz; scan speed: 150 to 1000 mm/s

- Barcode type:

CODE 39 or QR code; CODE 39 narrow width: 0.38 mm; QR code cell size: 0.508 mm

- Information carried by barcodes:

The mass value actually measured for a honeycomb structure

[0026] The ceramic honeycomb structure undergoes the barcode marking in the production process under such laser marking conditions as described above, and is then delivered to the process for carrying the catalytic component. Immediately before the catalytic component is carried, the barcodes marked on the ceramic honeycomb structure and the information about the mass thus marked is read by a barcode reader, and is transmitted to a device for carrying a catalyst. The honeycomb structure delivered into the device for carrying

a catalyst is carried with the catalytic component after the conditions have been adjusted on the basis of the specific information about the mass.

[0027] The honeycomb structure carried with the catalytic component is delivered to a catalyst baking process where it is processed at a temperature of about 600°C or higher. It is desirable to use an heat-resistant ink when the ink jet method is used, because there is an apprehension that the information displayed on the honeycomb structure will become unreadable or be burned owing to the discoloration of the honeycomb structure in the catalyst carrying process or the catalyst baking process.

[0028] In general, owing to masking, the catalytic component is not carried on the outer surface of the honeycomb structure, and accordingly the marked inscription such as the barcodes or the like does not come to be buried by the catalytic component, but some discoloration cannot be avoided; accordingly, it is necessary to specify the marking conditions for the barcodes or the like so that the marked inscription may be read. In the case of the laser marking, the member surface is decomposed and removed in a very shallow region, so that the honeycomb structure carried with the catalytic component by passing through the process for carrying it with the catalytic component is then delivered to the canning process.

[0029] The character information can be printed similarly to the barcodes by the ink jet method or the laser marking method. In this case, the printed character information is recorded by a CCD camera and recognized by a pattern matching method. This method is a method in which the characters are registered beforehand, and the patterns closest to the registered characters are selected from the dark and light information of the recorded characters. The present inventors made the numerical character information about the mass displayed by the above laser marking method be read on a F350 image recognition device manufactured by Omron Corp., and confirmed that the information was able to be transmitted without fail.

[0030] The reading principle of a barcode reader is that a laser light beam is irradiated on a barcode label and the diffuse reflection light therefrom is received by the light receiver in the barcode reader. In the diffuse reflection light, weak and strong intensities are generated by the reflectivity differences between the spaces and the bars, and such intensities are converted to the ON/OFF digital signals so that the spaces and bars are discriminated and read. Accordingly, in the case where even with the barcodes the weak and strong intensity differences (PCS) come to be small in the diffuse reflection light, reading on a barcode reader becomes difficult, and hence the above described image recognition processing method becomes effective.

[0031] Additionally, a method is possible in which the honeycomb structure is held in a metallic container before the catalytic component is carried, and then the

honeycomb structure is made to carry the catalytic component. According to this method, it is possible to avoid the trouble that the honeycomb structure is chipped or broken during the process for carrying the catalytic component. In this case, the masses of the compressive material and the metallic container are added to the mass of the honeycomb structure, and hence the total mass as an assembly becomes very heavier as compared to that of the honeycomb structure; thus, for the purpose of controlling the carried amount of the catalyst, the controlling becomes very difficult because the mass distributions both of the compressive material and of the metallic containers are added in addition to the mass distribution of the honeycomb structures. Accordingly, the control of the carried amount of the catalytic component becomes easy by adopting a way in which the information about the mass of the honeycomb structure is displayed on the outer surface of the metallic container, and the catalytic component is made to be carried on the basis of such information about the mass.

Industrial Applicability

[0032] As described above, according to the present invention, when a process is performed in which the cell structures are made to carry the catalytic component, the appropriate amount of the catalytic component in conformity with the mass of each cell structure can be carried even if the masses of the cell structures are distributed.

Claims

1. A processing method for carrying a cell structure with a catalytic component, **characterized by** displaying information about a mass of said cell structure is displayed on the surface thereof prior to the initiation of a carrying process, reading said information and carrying said cell structure with an appropriate amount of the catalytic component on the basis of the information, in the carrying process.
2. A processing method in which a cell structure, housed in and held by a metallic container through an intermediary of a cushioned compressive material, is made to carry thereon a catalytic component, **characterized by** displaying information about a mass of said cell structure is displayed on the surface thereof prior to the initiation of a carrying process, reading said information and carrying said cell structure with an appropriate amount of the catalytic component on the basis of the information, in the carrying process.
3. The processing method according to claim 1 or 2, in which the display manner of said information is of a character.
4. The processing method according to claim 1 or 2, in which the display manner of said information is of a barcode.
5. The processing method according to claim 3 or 4, in which said information is displayed with ink.
6. The processing method according to claim 5, in which the method displaying said information with ink is the ink jet method or the thermal transcription method.
7. The processing method according to claim 3 or 4, in which said information is displayed with a laser.
8. The processing method according to claim 3 or 4, in which said information is displayed with sand blast.
9. The processing method according to claim 3 or 4, in which said information is displayed with chemical corrosion action.
10. A cell structure processed by a processing method according to any one of claims 1 to 9.
11. A cell structure with information displayed thereon, which is processed by a processing method according to any one of claims 1 and 3 to 9.
12. The cell structure according to claim 10 or 11, which is a honeycomb structure having a plurality of cell passages defined by a plurality of partition walls and an outer circumferential wall surrounding the plurality of cell passages.
13. The cell structure according to claim 10 or 11, which is a foamed structure.
14. The cell structure according to claim 10 or 11, which is made of one ceramic material or a compound of two or more ceramic materials selected from the group consisting of cordierite, alumina, mullite, lithium aluminum silicate, aluminum titanate, titania, zirconia, silicon nitride, aluminum nitride, and silicon carbide.
15. The cell structure according to claim 10 or 11, which is made of one adsorptive material selected from a group consisting of activated charcoal, silica gel, and zeolite.

FIG. 1(a)




FIG. 1(b)





FIG. 2



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP01/09999

A. CLASSIFICATION OF SUBJECT MATTER Int.Cl. ⁷ B01J37/00, B21D47/00, F01N3/28		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) Int.Cl. ⁷ B01J21/00-38/74, B01D53/86, B01D53/94, B21D47/00, F01N3/28		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Jitsuyo Shinan Koho 1926-1996 Toroku Jitsuyo Shinan Koho 1994-2001 Kokai Jitsuyo Shinan Koho 1971-2001 Jitsuyo Shinan Toroku Koho 1996-2001		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) JOIS		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	JP 07-265706 A (Tokyo Roki K.K.), 17 October, 1995 (17.10.95), Par. Nos. [0047], [0061] (Family: none)	1-15
Y	JP 06-154710 A (Nippon Avionics Co., Ltd.), 03 June, 1994 (03.06.94), Par. Nos. [0008], [0009] (Family: none)	1-3, 10-15
Y	JP 08-001280 A (Hitachi Metals, Ltd.), 09 January, 1996 (09.01.96), Par. Nos. [0007], [0015] (Family: none)	1, 2, 4-15
Y	JP 07-005023 A (Kabushiki Kaisha Furukawa Seisakusho), 10 January, 1995 (10.01.95), Par. Nos. [0007], [0014] (Family: none)	1, 2, 4-15
Y	JP 05-123237 A (Matsushita Electric Ind. Co., Ltd.), 21 May, 1993 (21.05.93), Claim 8; Par. Nos. [0009], [0010] (Family: none)	5-9
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 13 December, 2001 (13.12.01)		Date of mailing of the international search report 25 December, 2001 (25.12.01)
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP01/09999

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	JP 08-173770 A (Matsushita Electric Ind. Co., Ltd.), 09 July, 1996 (09.07.96), Par. No. [0012] (Family: none)	10-15

Form PCT/ISA/210 (continuation of second sheet) (July 1992)